

#### **FEDERAL INDUSTRIES**

A Standex Company 215 Federal Avenue Belleville, WI 53508-9201

Phone: 800-356-4206 Fax: 608-424-3234

Email: geninfo@federalind.com Website: www.federalind.com

Project Name:	AIA#	
Item #:		
Model #:	Qty:	SIS#
Approval:		

## COUNTERTOP REFRIGERATED SELF-SERVE MERCHANDISER - BOTTOM MOUNT

The Signature Series counter top merchandiser combines attractive curved glass styling and merchandising flexibility. Designed for continuous case line-ups.





# **OPTIONAL ACCESSORIES**

- ☐ Glass Shelves
- $\hfill \square$  Reflective Ends
- □ Reflective Rear Doors
- ☐ Remote Refrigeration (EEV Included) on CRB Models Only
- □ LED Lighting

# MODEL | CRB3628SS | (Includes End Panels ) | | CRB3628SS | 36 x 29.7 x 40.5 (in) | | 914 x 754 x 1029 (mm) | | CRB4828SS | 48 x 29.7 x 40.5 (in) | | 1219 x 754 x 1029 (mm) |

### STANDARD FEATURES

#### **Model Features**

- Curved glass styling.
- Adjustable black metal shelf. Adjustable up and down and can also be tilted in two positions.
- Tempered front glass with self-serve cut out for customer access. Acrylic end panels.
- Removable sliding rear doors, shelf light, shelf supports, and shelf.
- Removable, scratch-resistant, rustproof black display deck.
- Easily accessible light switch and adjustable temperature control.
- Black painted metal and stainless construction. Black trim.
- Designed for continuous line-ups.
- Cord and plug (NEMA 5-15P).
- Installation Flexibility
- Recessed 3" in the counter with condensing component mounted underneath (CRB Models).

#### Refrigeration

- Average case temperature of 38° F (3.3° C) to 40° F (4.4° C) is maintained.
- Thermometer.
- R290 Refrigerant

#### Shelving

 Adjustable black metal shelf. Adjustable up and down and can also be tilted in two positions.

#### Lighting

• 3500K LED top light and shelf lights.

#### **Agency Approvals**

- UL Safety and UL Sanitation Listed
- DOE 2017 Compliant





# AIA#

SIS#

## COUNTERTOP REFRIGERATED SELF-SERVE MERCHANDISER - BOTTOM MOUNT


# **Product Specifications**

Intended Environment: Type I - Designed to operate in maximum ambient conditions of 75°F (24°C) and 55% relative humidity unless noted otherwise in system information below.

20.0	0.011									
Zo	one	Intended Product To Be Displayed	Avg Prod Temp °F/°C							
А	All	Packaged Refrigerated Products	38°F / (3.3°C)							

DIMENSION: xx"/(mm)

**DIMENSION TOLERANCE +/- 0.19 (4.8)** 



									SELF CONTAINED					
	DIMENSION				SHELVING			ELECTRICAL					SHIP	
140051	L	D	Ι	LS	# OF TIERS	D	L		2-WIRE + GROUND 120/60/1			DEEDLOEDANT	CONDENSATE	WEIGHT
MODEL	in	in	in	in		in	in		AMPS FI	MAX	STANDARD NEMA	REFRIGERANT	REMOVAL	LBS
	mm	mm	mm	mm		mm	mm			FUSE SIZE	CORD & PLUG			KILO
CRB3628SS	36.0	29.7	41.2	34.5	1	14.2	32.7	6.57	6	15 NEMA 5-15p	NEMA E 1En	R290a	CONDENSATE	400 LBS
CRB302833	914	754	1045	876		361	831				N290a	EVAPORATOR	181 KILO	
CRB4828SS	48.0	29.7	41.2	46.5	1	14.2	44.7	8.85	6	15 NEM	NEMA E 1Ep	R290a	CONDENSATE	460 LBS
	1219	754	1045	1181	1	361	1136				NEMA 5-15p		EVAPORATOR	209 KILO

- \* Height above counter
- If a GFCI circuit is required, a GFCI Breaker Must be used instead of GFCI receptacle.
- Refrigerated cases are designed to operate in a maximum of 75°F (24°C) ambient and 55% relative humidity.
- Due to continuing engineering improvements, specifications are subject to change without notice.









**Email:** Geninfo@Federalind.com **Website:** Federalind.com