

FEDERAL INDUSTRIES

A Standex Company 215 Federal Avenue Belleville, WI 53508-9201

Phone: 800-356-4206 Fax: 608-424-3234

Email: geninfo@federalind.com Website: www.federalind.com

Project Name:	AIA#
Item #:	
Model #: Qty:	SIS#
Approval:	

HYBRID MERCHANDISER

SERVICE NON-REFRIGERATED OVER SELF-SERVE REFRIGERATED

MODEL	DIMENSIONS
	(Includes End Panels)
□ CD3628/RSS3SC	36.25x 39 x 69.75 (in)
	921 x 991 x 1772 (mm)
□ CD4828/RSS4SC	48 x 39 x 69.75 (in)
	1219 x 991 x 1772 (mm)
□ (2)CD3628/RSS6SC	72 x 39 x 69.75 (in)
	1829 x 991 x 1772 (mm)

Display more product and serve more customers with presentation and value in mind.



OPTIONAL ACCESSORIES

For Top Display

- ☐ Glass Shelves
- □ Reflective Ends
- □ Reflective Rear Doors

For Self-Serve Refrigerated Base

- ☐ Energy Saving Night Curtain
- □ Silver Trim
- ☐ Special Base Finish
- ☐ Mirrored Interior Ends
- ☐ Security Night Cover
- ☐ Stainless Steel Steps in Lieu of Metal Shelves
- ☐ Reflective End Glass

SELF-SERVE NON-REFRIGERATED OVER SELF-SERVE REFRIGERATED

MODEL	DIMENSIONS (Includes End Panels)
□ CD3628SS/RSS3SC	36.25 x 39 x 69.75 (in)
	921 x 991 x 1772 (mm)
□ CD4828SS/RSS4SC	48 x 39 x 69.75 (in)
	1219 x 991 x 1772 (mm)
□ (2)CD3628SS/RSS6SC	72 x 39 x 69.75 (in)
	1829 x 991 x 1772 (mm)

STANDARD FEATURES

Refrigerated Self-Serve Bottom Display

- Black laminated exterior. Other finishes available.
- Black trim. Silver optional.
- Black interior, glass ends.
- Horizontal LED top and front light.
- Two tiers black metal shelves.
- Electronic temperature control maintains 38° to 40° case temperature. Note: Case temperature will vary if the air curtain is disrupted.
- Cord and plug. (Not available on RSS6SC.)
- Condensate evaporator (separate circuit required on model RSS6SC)
- R513a Refrigeratant

Service or Self-Serve Non-Refrigerated Top Display

- Two tiers black wire shelves.
- Sliding rear doors.
- Black trim.
- Self-Serve has three hinged lift-up front doors.

Lighting

LED top light and shelf lights.

Agency Approvals

- UL Safety and UL Sanitation Listed to NSF Type II conditions.
- DOE 2017 Complaint









AIA#

HYBRID MERCHANDISER

SIS#

Product Specifications

Intended Environment: Type I - Designed to operate in maximum ambient conditions of 75°F (24°C) and 55% relative humidity unless noted otherwise in system information below.

Zone	Intended Product To Be Displayed	Avg Prod Temp °F/°C
All	Packaged Refrigerated Products	38°F / (3.3°C)


DIMENSION: xx"/(mm)

DIMENSION TOLERANCE +/- 0.19 (4.8)

SERVICE NON-REFRIGERATED OVER SELF-SERVE REFRIGERATED

30.00 16.75 16.75 10.00 10

SELF-SERVE NON-REFRIGERATED OVER SELF-SERVE REFRIGERATED



MODEL	DIMENSIONS			SHIPPING WHT		BOTTOM DISPLAY	TOP DISPLAY			
	L	D	н	UNITS	LBS	KILO	120/60/1 (NEMA 5-20P)	120/60/1 (NEMA 5-15P)		
CD3628/RSS3SC	36.25	39	69.75	in.	847	847 384	1/3 HP - 14.8 AMPS	1.5 AMPS		
	921	991	1772	mm.						
CD4828/RSS4SC	48	39	69.75	in.	1,010	1.010 458	1/2 HP - 16.0 AMPS	1.5 AMPS		
	1219	991	1772	mm.		10 458				
(2)CD3628/RSS6SC*	72	39	69.75	in.	1,500	1,500 680	3/4 HP - 16.0 AMPS	(2) 1.5 AMPS		
	1829	991	1772	mm.						
CD3628SS/RSS3SC	36.25	39	69.75	in.	790	790 35	358	1/3 HP - 14.8 AMPS	1.5 AMPS	
	921	991	1772	mm.						
CD4828SS/RSS4SC	48	39	69.75	in.	900	900	000	408	1/2 HP - 16.0 AMPS	1.5 AMPS
	1219	991	1772	mm.			900 408	1/2 HF - 16.0 AIVIPS	T.J AIVIPS	
(2)CD3628SS/RSS6SC*	72	39	69.75	in.	1,300	1,300	1 200 500	3/4 HP - 16.0 AMPS	(2) 1.5 AMPS	
	1829	991	1772	mm.			590			

- * On the RSS6SC a separate 120/60/1 15 AMP circuit is required for the condensate evaporator.
- If a GFCI circuit is required, a GFCI Breaker Must be used instead of GFCI recepticle.
- Refrigerated cases are designed to operate in a maximum of 75°F (24°C) ambient and 55% relative humidity.
- Due to continuing engineering improvements, specifications are subject to change without notice.a









Phone: 800-356-4206 **Fax:** 608-424-3234

Email: Geninfo@Federalind.com **Website:** Federalind.com